



NOTE1. CONTACT PLATING
 GOLD(0.2μm MIN.) ON MATING AREA,
 TIN/LEAD ON TERMINATION AREA,
 ALL OVER NICKEL UNDERPLATED.

2. CABLE CHARACTERISTICS
 #20AWG MAX.

HONDA
 PRINT RM
 AUG.18.1997
 ISSUED

PCS-E68FS	68	52.1	1.27x(34-1)=41.91	45.88	HONDA PCS-E68FS	1,34,35,68
PCS-E50FS	50	40.7	1.27x(25-1)=30.48	34.45	HONDA PCS-E50FS	1,25,26,50
PCS-E36FS	36	31.8	1.27x(18-1)=21.59	25.56	HONDA PCS-E36FS	1,18,19,36
PCS-E28FS	28	26.7	1.27x(14-1)=16.51	20.48	HONDA PCS-E28FS	1,14,15,28
PCS-E20FS	20	21.65	1.27x(10-1)=11.43	15.4	HONDA PCS-E20FS	1,10,11,20
PART NO.	NO.OF POS.	A	B	△C	PART NO.	POS.NO.
DIMENSIONS				MARKING		

△				4	SPACER	PBT(GF)	2	—	UL94V-0 BLACK
△	AUG.18 1997	K.Y	DIM.	3	CONTACT	PHOSPHOR BRONZE	NO.OF POS.	NOTE#1	—
△	AUG.12 1997	K.Y	NEW REV.	2	SHELL	STEEL	1	Ni PLATING	—
△				1	INSULATOR	PBT(GF)	1	—	UL94V-0 BLACK
LTR.	DATE	BY	REV. DESCRIPT	NO.	PART NAME	MATERIAL	QTY	FINISH	NOTE
DATE DEC.03.1985		SCALE 2/1		UNIT mm(INCH)	3RD . A . P HONDA TSUSHIN KOGYO., LTD.				
DR	DE	CHK	CHK	APP	NAME	PCS-E TYPE FEMALE CONNECTOR			REV.
					PART NO.	PCS-E()FS			2B