


CONTACT DETAIL 5/1

NOTE 1. CONTACT PLATING  
 CONTACT AREA: GOLD 0.2μm MIN.  
 TERMINATION AREA: TIN/LEAD  
 UNDERPLATING: NICKEL



PCR-E96FS	96	69.9	61.61	1.27x (48-1) = 59.69	64.51	1, 48, 49, 96
PCR-E68FS	68	52.1	43.83	1.27x (34-1) = 41.91	46.73	1, 34, 35, 68
PCR-E50FS	50	40.7	32.4	1.27x (25-1) = 30.48	35.3	1, 25, 26, 50
PCR-E36FS	36	31.8	23.51	1.27x (18-1) = 21.59	26.41	1, 18, 19, 36
PCR-E28FS	28	26.7	18.43	1.27x (14-1) = 16.51	21.33	1, 14, 15, 28
PCR-E20FS	20	21.65	13.35	1.27x (10-1) = 11.43	16.25	1, 10, 11, 20
PART No.	No. OF POS.	A	B	C	D	CONTACT POS. # MARKING
DIMENSION						

△	APR. 30 1988	K. H	HONDA LOT PART No MARKING	4	SPACER	PPS (GF)	1	UL94V-0 BLACK
△	FEB. 6 1986	K. S	NEW REV.	3	SHELL	STEEL	1	NICKEL PLATING
△	LTR. DATE	BY	REV. DESCRIPT	2	INSULATOR	PBT (GF)	1	UL94V-0 BLACK
	DATE		NO.	1	CONTACT	PHOSPHOR BRONZE	No. OF POS.	SEE NOTE 1
	SCALE	UNIT	PART NAME				MATERIAL QTY	FINISH
	2 / 1	mm (INCH)						NOTE
	SEP. 7. 1988							
	APP. DATE & REV.							
	DR.	DE.	CHK.	CHK.	APP.			
				HONDA TSUSHIN KOGYO CO., LTD.				
				NAME				
				1.27mm SPACING SOLDER TYPE FEMALE CONNECTOR				
				PART NO. PCR-E ( ) FS				
				REV 2C				